Fluke 1587 FC and 1577 Insulation Multimeters





Fluke 1577









Two powerful tools in one.

The Fluke 1587 FC and 1577 Insulation Multimeters combine a digital 1 kV insulation tester with a full-featured, true-RMS digital multimeter in a single compact, handheld unit, which provides maximum versatility for both troubleshooting and preventive maintenance.

- Insulation test (1587 FC: 0.01 M Ω to 2 G Ω) (1577: 0.1 M Ω to 600 M Ω)
- Insulation test voltages (1587 FC: 50 V, 100 V, 250 V, 500 V, 1000 V), (1577: 500 V, 1000 V) for many applications
- Live circuit detection prevents insulation test if voltage > 30 V is detected for added user protection
- Auto-discharge of capacitive voltage for added user protection
- Filter for motor drive measurements (1587 FC only)
- AC/DC voltage, DC millivolts, AC/DC milliamps, resistance (Ω) , and continuity
- Capacitance, diode test, temperature, Min/Max, and frequency (Hz) (1587 FC only)
- Auto power off to save battery power
- · Large display with backlight and large digits
- Included accessories: Remote probe, test leads and probes, alligator clips, (Type K thermocouple, 1587 FC only)
- Accepts optional Fluke TPAK magnetic hanging system to free your hands for other work
- Rugged, utility hard case allows you to bring everything you need for the job
- Three-year warranty

The Fluke 1587 FC Insulation Multimeter adds four powerful diagnostic functions through the Fluke Connect™ Measurements app:

- PI/DAR timed ratio tests with TrendIt[™] graphs identifies moisture and contaminated insulation problems faster
- Memory storage through Fluke Connect[™] eliminates writing down results, reduces errors and saves data for historical tracking over time
- Temperature compensation through app for establishing accurate baselines and relevant historical comparisons

| Specifications | 1587 FC | 1577 |
|--|-------------------|------------------|
| Insulation test voltages 50 V, 100 V, 250 V, 500 V, 1000 V | • | |
| Insulation test voltages 500 V, 1000 V | | • |
| Insulation resistance | 0.01 MΩ to 2.0 GΩ | 0.1 MΩ to 600 MΩ |
| Auto-discharge of capacitive voltage | • | • |
| Insulation test smoothing reading | • | |
| Frequency | • | |
| Capacitance | • | |
| Diode test | • | |
| Temperature | • | |
| Min/Max | • | |
| Low-pass filter (for work on VSDs) | • | |
| AC/DC voltage | • | • |
| DC millivolts | • | • |
| AC/DC milliamps | • | • |
| Resistance | O.1 Ω to 50 MΩ | O.1 Ω to 50 MΩ |
| Continuity | • | • |
| Remote probe, test leads, alligator clips | • | • |
| Type K thermocouple | • | |
| Rugged, utility hard case | • | • |
| Auto power off | • | • |



Included Accessories

Remote Probe, Test Leads, Alligator Clips, K-type Thermocouple (1587 FC only), Hard Case, User Documentation.

Ordering Information

| Ordering Information | | |
|-------------------------------|---|--|
| FLUKE- 1577 | Insulation Multimeter | |
| FLUKE- 1587FC | Insulation Multimeter with Fluke Connect™ | |
| FLUKE- 1587/MDT FC Kit | FC 2-in-1 Adv Motor & Drive Kit w/ 9040, i400 | |
| FLUKE- 1587/I400 FC KIT | FC 2-in-1 Insulation Multimeter with i400 | |
| 1587KIT/ 62MAX+FC | FC 2-in-1 Adv Elec Kit w/62MAX+ i400 | |

Contact your local distributor for price and availability. fluke.com/wtb